

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	110V (stabilisation 3 min.)
MEASURING POSITION	Vertical
LIFE TEST POSITION	Horizontal
BURNING POSITION	P4
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	400W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2150 K NA
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
WEIGHT	33 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : 9245 137 31900 0833/000 p. 190-2 Of 07/07/2008		HALOGEN LAMP INFRARED INDUSTRIAL FACETTED 13939F-V 400W 110V CL						9245 137 31900 0833/000			22/11/2012				
REF. :	PDM IRK 2010-053	DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															