

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	230V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Vertical
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P4
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	400W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b>	Clear lamp Lamp with reflector	2250 K NA
<b>FLUX (HeLeN lamp)</b>	Clear lamp Reduction	NA NA
<b>WEIGHT</b>	33 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 137 44200		22/11/2012					
9245 137 44200		INFRARED INDUSTRIAL FACETTED						0833/000							
0833/000 p. 190-2		13939F-V 400W 230V CL													
Of 07/07/2008		REF. : PDM IRK 2010-053		DOCUMENTATION		UNIT	mm	PROJ EUROPE	2	SH	SH	190-2	10		A4
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															