

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	600V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

		VALUE UNIT	TOLERANCE
<b>WATTAGE</b>		1600W	± 6 %
<b>LIFE</b>		5000 h	average
<b>COLOR TEMPERATURE</b>	Clear lamp	2700 K	± 100 K
	Lamp with reflector	NA	
<b>FLUX (HeLeN lamp)</b>	Clear lamp	NA	
	Reduction	NA	
<b>WEIGHT</b>		62 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 339 51200			10/07/2013				
9245 339 51200		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		13252/99 1600W 600V CL													
Of 18/11/2003		REF. : PDM IRK 2013-035		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															