

PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	230V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	3000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2400 K 2300 K	± 100 K Indicative value
FLUX (HeLeN lamp)	NA	
WEIGHT	98 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 363 44200			22/03/2011				
9245 363 44200		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p. 190-2		14107Z/98 3000W 230V REFL													
Of 13/01/2004		REF. : PDM IRK 2010-053		DOCUMENTATION		UNIT	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															