

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal Free air burning
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2700 K 2600 K ± 100 K Indicative value
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
WEIGHT	45 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 561 49100			14/01/2013				
9245 561 49100		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p. 190-2		14143Z/98 2500W 400V REFL													
Of 08/07/2011		REF. : PDM IRK 2012-060		DOCUMENTATION		UNIT	PROJ EUROP	2	SH	SH	190-2	10		A4	
		NOM : J.P. CHARLIER		VALIDATION : A. PICHARD				DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															