

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		2000W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp	2700 K	± 100 K
	Lamp with reflector	2600 K	Indicative value
FLUX (HeLeN lamp)	Clear lamp	NA	
	Reduction	NA	
WEIGHT		47 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 793 49100			15/01/2013				
9245 793 49100		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p. 190-2		14188Z/98 2000W 400V REFL													
Of 22/09/2011		REF. : PDM IRK 2012-060		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															