

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		1500W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2300 K NA	± 100 K
FLUX (HeLeN lamp)	Clear lamp Reduction	10000 lm 95 %	Indicative value min
CAP INSULATION (WET)		2000 V	mini
WEIGHT		53 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 866 44900			20/07/2012				
9245 866 44900		INFRARED HeLeN						0833/000							
0833/000 p. 190-2		15091Z 1500W 235V													
Of 04/10/2010															
REF. :	PDM IRK 2011-016	DOCUMENTATION	UNIT	PROJ EUROP	2	SH	SH	190-2	10		A4				
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															