


**PRODUCT REQUIREMENT SHEET**

See LV 75-032

<b>MEASURING VOLTAGE</b>	235V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	1600W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b> Clear lamp Lamp with reflector	2700 K 2600 K	± 100 K Indicative value
<b>FLUX (HeLeN lamp)</b>	NA	NA
<b>IRRADIANCE LEVEL</b>	20000 W/m <sup>2</sup>	mini
<b>WEIGHT</b>	35 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : 9245 901 44900 0833/000 p. 190-2 Of 02/09/2011		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 14213Z/83 1600W 235V REFL						9245 901 44900 0833/000			06/03/2012				
REF. :	PDM IRK 2012-007	DOCUMENTATION	UNIT mm	PROJ EUROP 	2	SH	SH	190-2	10		A4				
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															