

PRODUCT REQUIREMENT SHEET

See LV 75-032

| | |
|---------------------------|-----------------------------|
| MEASURING VOLTAGE | 400V (stabilisation 3 min.) |
| MEASURING POSITION | Horizontal |
| LIFE TEST POSITION | Vertical Free air burning |
| BURNING POSITION | Any |
| SWITCHING CYCLE | Continuous |
| AGEING | 1h at rated voltage |

| | | VALUE UNIT | TOLERANCE |
|--------------------------|---------------------|------------|-----------|
| WATTAGE | | 3000W | ± 6 % |
| LIFE | | 5000 h | average |
| COLOR TEMPERATURE | Clear lamp | 2650 K | ± 100 K |
| | Lamp with reflector | NA | |
| FLUX (HeLeN lamp) | Clear lamp | NA | |
| | Reduction | NA | |
| WEIGHT | | 48 g | |

| | | | | | | | | | | | | | | | |
|---|---------------|---|------------|-------------|------|----|--------------------|-------|----|----------------|--|---|------------|----|--|
| 1 | 0833 | 2 | 0833 | 3 | 0000 | 4 | | 5 | | 6 | | 7 | | 8 | |
| SUPERSEDES : | | HALOGEN LAMP INFRARED INDUSTRIAL 14219X 3000W 400V CL | | | | | | | | 9245 917 49100 | | | 02/03/2012 | | |
| Nouvelle | | | | | | | | | | 0833/000 | | | | | |
| REF. : | CRP 1202 | DOCUMENTATION | UNIT mm | PROJ EUROPE | 2 | SH | SH | 190-2 | 10 | | | | | A4 | |
| NOM : | J.P. CHARLIER | VALIDATION : A. PICHARD | | | | | DR. FISCHER Europe | | | | | | | | |
| All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner. | | | | | | | | | | | | | | | |