


PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2500 K NA	± 100 K
IRRADIANCE LEVEL	16000 W/m ²	Mini
WEIGHT	38 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 920 44900			14/04/214				
9245 920 44900		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p.190-2		13168V/83 2000W 235V REFL													
Of 17/10/2013		DOCUMENTATION		UNIT	PROJ EUROP	2	SH	SH	190-2	10			A4		
REF. : SLH/MS3/I1205				mm											
NOM : PI120		VALIDATION : SN928				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															