

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	235V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Vertical
<b>BURNING POSITION</b>	Any
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE	
<b>WATTAGE</b>	2000W	± 6 %	
<b>LIFE</b>	5000 h	average	
<b>COLOR TEMPERATURE</b>	Clear lamp Lamp with reflector	2500 K NA	± 100 K
<b>FLUX (HeLeN lamp)</b>	Clear lamp Reduction	18000 lm 95 %	Indicative value min
<b>CAP INSULATION (WET)</b>	2000 V	mini	
<b>WEIGHT</b>	47 g		

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 949 44900			19/03/2014				
9245 949 44900		INFRARED HeLeN						0833/000							
833/000 p190-2		15114A 2000W 235V													
Of 17/05/2013		REF. : MS3/CRP1310		DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10			A4		
NOM : PI120		VALIDATION : SN928				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															