

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	400V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	2000W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b>	Clear lamp Lamp with reflector	2700 K 2600 K ± 100 K Indicative value
<b>FLUX (HeLeN lamp)</b>	Clear lamp Reduction	NA NA
<b>IRRADIANCE LEVEL</b>	16000 W/m <sup>2</sup>	Mini
<b>WEIGHT</b>	47 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 14229Z/83 2000W 400V REFL								9245 950 49100			24/05/2013		
New										0833/000					
REF. :	CRP 1317	DOCUMENTATION	UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															