

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp 2300 K Lamp with reflector 2200 K	± 100 K Indicative value
FLUX (HeLeN lamp)	Clear lamp NA Reduction NA	
MAXIMUM IRRADIANCE LEVEL AT 10 CM	xxxxx W/m ²	Min
WEIGHT	100 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 13993Z/83 1500W 235V REFL								9245 978 44900			21/01/2014		
New										0833/000					
REF. :	CRP 1402	DOCUMENTATION	UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD					DR. FISCHER Europe								
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															