

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp HeLeNLamp	2450 K NA	± 100 K
FLUX (HeLeN lamp) Clear lamp Reduction	20000 lm 95 %	Indicative value min
CAP INSULATION (WET)	2000 V	min
WEIGHT	77 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED HeLeN 15120Z 2000W 235V								9245 985 44900 0833/000			18/03/2014		
New		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10			A4		
REF. : CRP 1413		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															