

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2300 K NA ± 100 K
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
WEIGHT	38 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 14248X/98 1500W 235V REFL						9246 005 44900			24/11/2014				
New								0833/000							
REF. :	CRP 1421	DOCUMENTATION	UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10		A4				
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															