

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	120V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp HeLeN Lamp	2500 K NA	± 100 K
FLUX (HeLeN lamp) Clear lamp Reduction	12000 lm 95 %	Indicative value min
CAP INSULATION (WET)	2000 V	Mini
WEIGHT	43 g	

Projet

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED HeLeN 15126Z 1500W 120V								9246 060 36300 0833/000			24/02/2016		
New		DOCUMENTATION		UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10			A4		
REF. : CRP 1606		VALIDATION : A. PICHARD				DR. FISCHER Europe									
NOM : J.P. CHARLIER															
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															