

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	120V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	500W	± 6 %
<b>LIFE</b>	6000 h	average
<b>COLOR TEMPERATURE</b> Clear lamp Lamp with reflector	2500 K NA	± 100 K
<b>FLUX (HeLeN lamp)</b>	NA	
<b>WEIGHT</b>	30 g	

Projet

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL 500T3LL 500W 120V TRL								9246 064 36300			03/03/2016		
New										0833/000					
REF. :	CRP 1610	DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															