

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2500 K 2400 K	± 100 K Indicative value
FLUX (HeLeN lamp)	NA	
MAXIMUM IRRADIANCE LEVEL AT 10 CM	9400 W/m ² *	Min
WEIGHT	48 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9246 075 44900			16/05/2017				
9246 075 44900		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p190-2		14283Z/83 1000W 235V REFL													
Of 10/05/2016		DOCUMENTATION		UNIT	PROJ EUROPE	2	SH	SH	190-2	10			A4		
REF. :	PDM IRK 2017-014	VALIDATION : A. PICHARD				DR. FISCHER Europe									
NOM :	J.P. CHARLIER	All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.													