

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	480V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2700 K 2600 K	± 100 K Indicative value
FLUX (HeLeN lamp) Clear lamp Reduction	NA NA	
PERMISSIBLE PINCH TEMPERATURE	350 °C	Maxi (in application)
PERMISSIBLE BULB TEMPERATURE	900 °C 250 °C	Maxi (in application) Mini (in application)
MAXIMUM IRRADIANCE LEVEL AT 10 CM	8500W/m ²	Min
WEIGHT	45 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 14288Z/83 1000W 480V REFL								9246 085 51700			08/07/2016		
New										0833/000					
REF. :	CRP 1625	DOCUMENTATION	UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															