

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	230V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE	
WATTAGE	500W	± 8 %	
LIFE	2000 h	average	
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2900 K NA	Indicative value
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA	
IRRADIANCE LEVEL	7500 W/m ²	mini	
WEIGHT	35 g		

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 30014Z/83 500W 230V REFL								9246 126 44200 0833/000			19/05/2017		
New		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10			A4		
REF. : CRP 1723		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															