

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE	
WATTAGE	2000W	± 6 %	
LIFE	5000 h	average	
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2450 K 2350 K	± 100 K Indicative value
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA	
MAXIMUM IRRADIANCE LEVEL AT 10 CM	11000 W/m <sup>2</sup>	Min	
WEIGHT	77 g		

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 30015Z/83 2000W 400V REFL								9246 127 49100			19/05/2017		
New										0833/000					
REF. :	CRP 1724	DOCUMENTATION	UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD					DR. FISCHER Europe								
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															