

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		3000W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp	2650 K	± 100 K
	Lamp with reflector	2550 K	Indicative value
FLUX (HeLeN lamp)	Clear lamp	NA	
	Reduction	NA	
WEIGHT		40 g	

Projet

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 30019Z/98 3000W 235V REFL								9246 131 44900			19/06/2017		
New										0833/000					
REF. :	CRP 1828	DOCUMENTATION	UNIT mm	PROJ EUROPE	2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD					DR. FISCHER Europe								
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															