

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1500W	± 6 %
LIFE Horizontal P15 (in certified fixture) *	10000 h	average
LIFE in other position *	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2300 K NA	± 100 K
FLUX (HeLeN lamp) Clear lamp Reduction	10000 lm 95 %	Indicative value min
CAP INSULATION (WET)	2000 V	mini
WEIGHT	53 g	

Projet

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9246 134 44900			27/06/2017				
9246 134 44900		INFRARED HeLeN LL						0833/000							
0833/000 p190-2		25002Z 1500W 235V													
Of 23/06/2017		REF. : PDM IRK 2017-035		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10	A4		
NOM : PI120		VALIDATION : SN928						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															