

PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	3000 W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2700 K 2600 K	± 100 K Indicative
MAXIMUM IRRADIANCE LEVEL AT 10 CM	19000 W/m ²	Mini
WEIGHT	82 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : New		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 30021Z/83 3000W 400V REFL						9246 138 49100 0833/000			07/09/2017				
REF. :	MS2/I16060	DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4				
NOM :	J.-J. FREY	VALIDATION :	A. PICHARD		DR. FISCHER Europe										
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															