

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	400V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	4500W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b> Clear lamp Lamp with reflector	2600 K 2500 K	± 100 K Indicative value
<b>MAXIMUM IRRADIANCE LEVEL AT 10 CM</b>	18000 W/m <sup>2</sup>	Mini
<b>WEIGHT</b>	94 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : New		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 30029Z/83 4500W 400V REFL						9246 148 49100 0833/000			25/10/2017				
REF. :	I16015-22 ET2	DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4				
NOM :	J.-J. FREY	VALIDATION :	A. PICHARD		DR. FISCHER Europe										
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															