


PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2700 K 2600 K	± 100 K Indicative value
MAXIMUM IRRDIANCE LEVEL AT 10 CM	23000 W/m ² *	Mini
GHT	44 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : 9246 151 44900 0833/000 p190-1 Of 27/10/2017		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 30030Z/83 2500W 235V REFL						9246 151 44900 0833/000			04/12/2017				
REF. :	PDM IRK 2017-054	DOCUMENTATION	UNIT mm	PROJ EUROP 	2	SH	SH	190-2	10		A4				
NOM :	J.P. CHARLIER	VALIDATION :	A. PICHARD			DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															