



# CorePro LED PLC 2P



## CorePro LED PLC 6.5W 840 2P G24d-2

The CorePro LED PLC 2P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplamping in general lighting applications: it meets basic lighting requirements, offers significant energy savings and is environmentally friendly.

### Product data

General information	
Cap base	G24D-2 [G24d-2]
Nominal lifetime	30,000 h
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light technical	
Colour Code	840 [CCT of 4000K]
Beam angle (nom.)	120 degree(s)
Luminous Flux	700 lm
Colour designation	Cool White (CW)
Correlated Colour Temperature	4000 K
Luminous Efficacy (rated) (Nom)	92.31 lm/W
Colour consistency	<6
Colour rendering index (CRI)	83
LLMF at end of nominal lifetime (nom.)	70 %
Operating and electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	6.5 W
Starting time (nom.)	0.5 s

Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (nom.)	220-240 V
Temperature	
Ambient temperature range	-20 °C to 35 °C
T-Case maximum (nom.)	65 °C
Controls and dimming	
Dimmable	No
Mechanical and housing	
Bulb material	Plastic
Product length	100 mm
Bulb shape	Tube, single-ended
Approval and application	
Energy Efficiency Class	F
Energy-saving product	Yes
Approval marks	TUV CE marking RoHS compliance KEMA Keur certificate
Energy consumption kWh/1,000 hours	7 kWh
EPREL registration number	403557

# CorePro LED PLC 2P

CE mark	Yes
EU RoHS compliant	Yes
<b>Product data</b>	
Full EOC	871869654129600
Order product name	CorePro LED PLC 6.5W 840 2P G24d-2
Order code	54129600



SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
Material number (12NC)	929001201502
Full product name	CorePro LED PLC 6.5W 840 2P G24d-2
EAN/UPC - Case	8718696541302

## Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLC 6.5W 840 2P G24d-2	24.3 mm	28.4 mm	105.8 mm	125 mm	147.6 mm

## Photometric data



General uniform lighting - CorePro LED PLC 6.5W 840 2P G24d-2



Spectral Power Distribution Colour - CorePro LED PLC 6.5W 840 2P G24d-2



Light Distribution Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



# CorePro LED PLC 2P

## Lifetime




Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

Lumen Maintenance Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



Lumen Maintenance Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

## CorePro LED PLC 2P

