



CorePro LED PLC 2P



CorePro LED PLC 4.5W 830 2P G24d-1

The CorePro LED PLC 2P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplamping in general lighting applications: it meets basic lighting requirements, offers significant energy savings and is environmentally friendly.

Product data

General information	
Cap base	G24D-1 [G24d-1]
Nominal lifetime	30,000 h
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light technical	
Colour Code	830 [CCT of 3000K]
Beam angle (nom.)	120 degree(s)
Luminous Flux	475 lm
Colour designation	White (WH)
Correlated Colour Temperature	3000 K
Luminous Efficacy (rated) (Nom)	105.00 lm/W
Colour consistency	<6
Colour rendering index (CRI)	83
LLMF at end of nominal lifetime (nom.)	70 %
Operating and electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	4.5 W
Starting time (nom.)	0.5 s


Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (nom.)	220-240 V
Temperature	
Ambient temperature range	-20 °C to 35 °C
T-Case maximum (nom.)	60 °C
Controls and dimming	
Dimmable	No
Mechanical and housing	
Bulb material	Plastic
Product length	100 mm
Bulb shape	Tube, single-ended
Approval and application	
Energy Efficiency Class	F
Energy-saving product	Yes
Approval marks	TUV CE marking RoHS compliance KEMA Keur certificate
Energy consumption kWh/1,000 hours	5 kWh
EPREL registration number	403560

CorePro LED PLC 2P

CE mark	Yes
EU RoHS compliant	Yes
Product data	
Full EOC	871869670659600
Order product name	CorePro LED PLC 4.5W 830 2P G24d-1
Order code	70659600



SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
Material number (12NC)	929001350702
Full product name	CorePro LED PLC 4.5W 830 2P G24d-1
EAN/UPC - Case	8718696706602

Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLC 4.5W 830 2P G24d-1	24.3 mm	28.4 mm	95.8 mm	115 mm	137.6 mm

Photometric data



General uniform lighting - CorePro LED PLC 4.5W 830 2P G24d-1



Spectral Power Distribution Colour - CorePro LED PLC 4.5W 830 2P G24d-1




Light Distribution Diagram

CorePro LED PLC 2P


Lifetime



Life Expectancy Diagram




Life Expectancy Diagram - CorePro LED PLC 4.5W 830 2P G24d-1



Life Expectancy Diagram

Lumen Maintenance Diagram



Lumen Maintenance Diagram - CorePro LED PLC 4.5W 830 2P G24d-1

CorePro LED PLC 2P

