



CorePro LED tube Universal T8

CorePro LEDtube UN 1500mm HO 23W840 T8

The new Philips CorePro LEDtube Universal T8 brings simplicity to your lighting project. You don't need to pay attention to the driver technology anymore. Thanks to a unique design, Philips CorePro LEDtube Universal T8 directly fits in luminaires operating either on Electro Magnetic ballasts or HF Electronic ballasts or mains power connection. So simple to operate and no need to carry double stock of products! Perfectly safe, reliable & easy to install Philips CorePro LEDtube Universal T8 is the ideal alternative to standard fluorescent tubes to save energy and lower investment.

Product data

General information		LLMF at end of nominal lifetime (nom.) 70 %	
Cap base	G13 [Medium Bi-Pin Fluorescent]	Operating and electrical	
Nominal lifetime	50,000 h	Line Frequency	50 to 60 Hz
Switching Cycle	50,000	Input frequency	50 to 60 Hz
Lighting Technology	LED	Power Consumption	23 W
Flux measurement reference	Sphere	Lamp current (nom.)	130 mA
Light technical		Starting time (nom.)	0.5 s
Colour Code	840 [CCT of 4000K]	Warm-up time to 60% light	0.5 s
Beam angle (nom.)	240 degree(s)	Power Factor (Fraction)	0.9
Luminous Flux	2,700 lm	Voltage (nom.)	220-240 V
Colour designation	Cool White (CW)	Temperature	
Correlated Colour Temperature	4000 K	T-Case maximum (nom.)	60 °C
Luminous Efficacy (rated) (Nom)	117 lm/W		
Colour consistency	<6		
Colour rendering index (CRI)	80		

CorePro LED tube Universal T8

Controls and dimming

Dimmable	No
----------	----

Mechanical and housing

Lamp Finish	Frosted
Bulb material	Glass
Product length	1,500 mm
Bulb shape	Tube, double-ended

Approval and application


Energy-saving product	Yes
Approval marks	RoHS compliance TUV CE marking KEMA Keur certificate
Energy consumption kWh/1,000 hours	23 kWh
EPREL registration number	1,315,791

CE mark	Yes
EU RoHS compliant	Yes

Product data



Full EOC	871869680174100
Order product name	CorePro LEDtube UN 1500mm HO 23W840 T8
Order code	80174100
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
Material number (12NC)	929001869602
Net weight	0.270 kg
Full product name	CorePro LEDtube UN 1500mm HO 23W840 T8
EAN/UPC – Case	8718696801758

Dimensional drawing



Product	D1	D2	A1	A2	A3
CorePro LEDtube UN 1500mm HO 23W840 T8	27.9 mm	28 mm	1,500 mm	1,505.9 mm	1,514.2 mm


Photometric data



Spectral Power Distribution Colour



CorePro LED tube Universal T8

Photometric data





Light Distribution Diagram

Lifetime



Lumen Maintenance Diagram

Life Expectancy Diagram - CorePro LEDtube UN 1500mm HO 23W840 T8




Life Expectancy Diagram

Life Expectancy Diagram

CorePro LED tube Universal T8

Lifetime



Lumen Maintenance Diagram - CorePro LEDtube UN 1500mm HO 23W840 T8

