



CorePro GLASS LED candles and lusters

CorePro LEDLusterND6.5-60W P45 E27827CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information		Operating and Electrical	
Cap-Base	E27 [E27]	Line Frequency	50 to 60 Hz
Nominal lifetime	15,000 hour(s)	Input Frequency	50 to 60 Hz
Switching Cycle	20,000	Power Consumption	6.5 W
Lighting Technology	LED	Lamp Current (Nom)	50 mA
Flux measurement reference	Sphere	Wattage Equivalent	60 W
		Starting Time (Nom)	0.5 s
		Warm-up time to 60% light	0.5 s
		Power Factor (Fraction)	0.55
		Voltage (Nom)	220-240 V
Light Technical		Temperature	
Color Code	827 [CCT of 2700K]	T-Case Maximum (Nom)	55 °C
Luminous Flux	806 lumen		
Color Designation	Warm White (WW)	Controls and Dimming	
Correlated Color Temperature (Nom)	2700 K	Dimmable	No
Luminous Efficacy (rated) (Nom)	124.00 lm/W		
Color Consistency	<6		
Color rendering index (CRI)	80		
LLMF At End Of Nominal Lifetime (Nom)	70 %		

CorePro GLASS LED candles and lusters

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	P45 [P 45mm]

Approval and Application


Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	387451
CE mark	Yes
EU RoHS compliant	Yes

Product Data

Full product code	871951434766300
-------------------	-----------------



Order product name	CorePro LEDLusterND6.5-60W P45 E27827CLG
Order code	929002029092
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929002029092
Full product name	CorePro LEDLusterND6.5-60W P45 E27827CLG
EAN/UPC - Case	8719514347670

Dimensional drawing



Product	D	C
CorePro LEDLusterND6.5-60W P45 E27827CLG	45 mm	78 mm

Photometric data




General uniform lighting - CorePro LEDLusterND6.5-60W P45 E27827CLG

Light Distribution Diagram - CorePro LEDLusterND6.5-60W P45 E27827CLG


CorePro GLASS LED candles and lusters

Photometric data



Spectral Power Distribution Colour - CorePro LEDLusterND6.5-60W P45 E27827CLG

Lifetime



Lumen Maintenance Diagram - CorePro LEDLusterND6.5-60W P45 E27827CLG



Life Expectancy Diagram - CorePro LEDLusterND6.5-60W P45 E27827CLG

