



Corepro Glass High Lumen bulbs



CorePro LEDBulbND 120W E27 A67 865 FR G

CorePro, LEDbulb, A67, 120 W, E27, 6500 K, 2000 lm, CRI 80, 15000 hour(s), Glass

CorePro, LEDbulb, A67, 120 W, E27, 6500 K, 2000 lm, CRI 80, 15000 hour(s), Glass, 153.00 lm/W, EEL D, PF 0.51, Beam angle 300 degree(s), RG1, IP20, SVM 0.4, PstLM 1

Product data

General Information	
Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LEDbulb
Flux measurement reference	Sphere
Warranty period	2 years
Light Technical	
Color Code	865 [CCT of 6500K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	2,000 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	153.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %


Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	13 W
Lamp Current (Nom)	120 mA
Wattage Equivalent	120 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	60 °C
Controls and Dimming	
Dimmable	No

Corepro Glass High Lumen bulbs

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Glass
Bulb Shape	A67
Net Weight (Piece)	0.040 kg
Approval and Application	
Energy Efficiency Class	D
Energy Consumption kWh/1000 h	13 kWh
EPREL Registration Number	374904
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C



Application Conditions	
can it be used in closed luminaires	No
Wireless Technology	Not applicable
Product Data	
Order product name	CorePro LEDBulbND 120W E27 A67 865 FR G
Full product name	CorePro LEDBulbND 120W E27 A67 865 FR G
Full product code	871951434657400
Order code	929002372002
Material Nr. (12NC)	929002372002
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514346574
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514346581

Dimensional drawing



Product	D	C
CorePro LEDBulbND 120W E27 A67 865 FR G	70 mm	121 mm

Photometric data




General uniform lighting - CorePro LEDBulbND 120W E27 A67 865 FR G

Spectral Power Distribution Colour - CorePro LEDBulbND 120W E27 A67 865 FR G


Corepro Glass High Lumen bulbs

Photometric data




Light Distribution Diagram - CorePro LEDBulbND 120W E27 A67 865 FR G

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LEDBulbND 120W E27 A67 865 FR G

