



CorePro LEDcapsule LV



CorePro LEDcapsuleLV 2.7-28W G4 827

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information	
General information	
Lighting Technology	LED
Flux measurement reference	Sphere
Switching Cycle	50,000
Nominal lifetime	15,000 hour(s)
Cap-Base	G4 [G4]
Light Technical	
Color Code	827 [CCT of 2700K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	315 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	116.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	- Hz

Input Frequency	- Hz
Power Consumption	2.7 W
Lamp Current (Nom)	340 mA
Wattage Equivalent	28 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.65
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	85 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	Capsule
Approval and Application	
Energy Efficiency Class	F

Datasheet, 2023, July 3 data subject to change

CorePro LEDcapsule LV


Suitable For Accent Lighting	No	
Energy Consumption kWh/1000 h	3 kWh	
EPREL Registration Number	374875	
CE mark	Yes	
EU RoHS compliant	Yes	

Order code	929002389202	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	12	
Material number (12NC)	929002389202	
Full product name	CorePro LEDcapsuleLV 2.7-28W G4 827	
EAN/UPC - Case	8718699767761	

Product Data


Full product code	871869976775400	
Order product name	CorePro LEDcapsuleLV 2.7-28W G4 827	

Dimensional drawing



Product	D	С
CorePro LEDcapsuleLV 2.7-28W G4 827	15 mm	40 mm

Photometric data




Calculus Photometrica 4.5 Philips Lighting &V. Page: UT

80 20 200 300 400 500 600 700 800 \(\lambda[\text{nm}]\) \(\text{-}\t

Spectral Power Distribution Colour - CorePro LEDcapsuleLV 2.7-28W G4 827

General uniform lighting - CorePro LEDcapsuleLV 2.7-28W G4 827





Light Distribution Diagram - CorePro LEDcapsuleLV 2.7-28W G4 827

100

CorePro LEDcapsule LV

Lifetime





Life Expectancy Diagram - CorePro LEDcapsuleLV 2.7-28W G4 827

Lumen Maintenance Diagram - CorePro LEDcapsuleLV 2.7-28W G4 827

