



CorePro LEDcapsule LV



CorePro LEDcapsuleLV 1.8-20W GY6.35 827

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information	
Lighting Technology	LED
Flux measurement reference	Sphere
Switching Cycle	50,000
Nominal lifetime	15,000 hour(s)
Cap-Base	GY6.35 [GY6.35]
Light Technical	
Color Code	827 [CCT of 2700K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	205 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	113.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM)	0.4
Stroboscopic effect value (SVM)	1

Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	1.8 W
Lamp Current (Nom)	260 mA
Wattage Equivalent	20 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.6
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	80 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	Capsule

Datasheet, 2023, July 6 data subject to change


CorePro LEDcapsule LV

Approval and Application	
Energy Efficiency Class	F
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	2 kWh
EPREL Registration Number	374877
CE mark	Yes
EU RoHS compliant	Yes

Product Data	
Full product code	871869976779200


Order product name	CorePro LEDcapsuleLV 1.8-20W GY6.35 827	
Order code	929002389702	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	12	
Material number (12NC)	929002389702	
Full product name	CorePro LEDcapsuleLV 1.8-20W GY6.35 827	
EAN/UPC - Case	8718699767808	

Dimensional drawing




Product	D	С
CorePro LEDcapsuleLV 1.8-20W GY6.35 827	13 mm	35 mm

Photometric data



Calculus Phonometrics 4.5 Philips Lighting 6.V. Page: UT


General uniform lighting - CorePro LEDcapsuleLV 1.8-20W GY6.35 827



Light Distribution Diagram - CorePro LEDcapsuleLV 1.8-20W GY6.35 827


CorePro LEDcapsule LV


Photometric data



Spectral Power Distribution Colour - CorePro LEDcapsuleLV 1.8-20W GY6.35 827

Lifetime





Life Expectancy Diagram - CorePro LEDcapsuleLV 1.8-20W GY6.35 827

Lumen Maintenance Diagram - CorePro LEDcapsuleLV 1.8-20W GY6.35 827



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.