



CorePro LEDcapsule MV



CorePro LEDcapsule 3.2-40W ND G9 830

The LED specialties deliver a high quality light to make themselves to be a true replacement of halogen specialty lamp (such as G9 and R7S). It is particularly suit for task lighting in hotel and restaurants, and ideal for decorative and ambient application. LEDspecialty products deliver huge energy saving and minimize maintenance costs, without any compromise on light quality.

Product data

General Information	
Lighting Technology	LED
Flux measurement reference	Sphere
Switching Cycle	8,000
Nominal lifetime	15,000 hour(s)
Cap-Base	G9 [G9]
Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	400 lumen
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	125.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	0.4

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	3.2 W
Lamp Current (Nom)	30 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	82 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear


Datasheet, 2023, July 6 data subject to change

CorePro LEDcapsule MV

Bulb Shape	Capsule
Approval and Application	
Energy Efficiency Class	E
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	4 kWh
EPREL Registration Number	453191
CE mark	Yes
EU RoHS compliant	Yes
Product Data	
Full product code	871951430395900


Order product name	CorePro LEDcapsule 3.2-40W ND G9 830	
Order code	929002495602	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	12	
Material number (12NC)	929002495602	
Full product name	CorePro LEDcapsule 3.2-40W ND G9 830	
EAN/UPC - Case	8719514303966	

Dimensional drawing




Product	D	С
CorePro LEDcapsule 3.2-40W ND G9 830	16.5 mm	54 mm

Photometric data






General uniform lighting - CorePro LEDcapsule 3.2-40W ND G9 830



Light Distribution Diagram - CorePro LEDcapsule 3.2-40W ND G9 830


CorePro LEDcapsule MV


Photometric data



Spectral Power Distribution Colour - CorePro LEDcapsule 3.2-40W ND G9 830

Lifetime





Life Expectancy Diagram - CorePro LEDcapsule 3.2-40W ND G9 830

Lumen Maintenance Diagram - CorePro LEDcapsule 3.2-40W ND G9 830



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.