



# E A C

# CorePro Plastic LEDcandles & lusters

## CorePro lustre ND 7-60W E27 827 P48 FR

The CorePro LEDcandles and lusters are designed for retrofit replacement of incandescent lamps and are particularly attractive for chandeliers. They are compatible with fixtures with an E14 holder for candles and E14 or E27 holders for lusters and are available in multiple color temperatures. LED lamps deliver huge energy savings of up to 80% energy-saving compared with halogen lamps and provide excellent quality of light. By offering a lifetime of 15,000 hours it lowers maintenance costs. The CorePro LED candles and lusters are perfect for your basic lighting needs.

### **Product data**

General Information	
Cap-Base	E27 [E27]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux	806 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	115.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	7 W
Lamp Current (Nom)	59 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	83 ℃
Controls and Dimming	
Dimmable	No

Datasheet, 2023, June 6 data subject to change

# CorePro Plastic LEDcandles & lusters

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	P48 [P 48mm]
Approval and Application	
Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	453213
CE mark	Yes
EU RoHS compliant	Yes


871951431302600
CorePro lustre ND 7-60W E27 827 P48 FR
929002973002
1
10
929002973002
CorePro lustre ND 7-60W E27 827 P48 FR
8719514313033

# Dimensional drawing




Product	D	С
CorePro lustre ND 7-60W E27 827 P48 FR	48 mm	95 mm

#### Photometric data




Light Distribution Diagram - CorePro lustre ND 7-60W E27 827 P48 FR



Spectral Power Distribution Colour - CorePro lustre ND 7-60W E27 827 P48 FR

# CorePro Plastic LEDcandles & lusters


#### Photometric data




Calculus Preconector 4.5 Philips Lighting E.V. Pages 19

General uniform lighting - CorePro lustre ND 7-60W E27 827 P48 FR

#### Lifetime





Life Expectancy Diagram - CorePro lustre ND 7-60W E27 827 P48 FR

Lumen Maintenance Diagram - CorePro lustre ND 7-60W E27 827 P48 FR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.