



CorePro LED tube EM/ Mains T8



CorePro LEDtube 600mm 8W 830 T8

CorePro, LEDtube, T8, EM/Mains, 600 mm, 8 W, 18W TL-D, 3000 K, 750 lm, CRI 80, 50000 hour(s)

CorePro, LEDtube, T8, EM/Mains, 600 mm, 8 W, LED alternative to 18W TL-D, 3000 K, 750 lm, CRI 80, 50000 hour(s), 93 lm/W, EEL F, G13, Beam angle 240 degree(s), Glass, 600 mm, RG0, SDCM 6, PF 0.9, IP20, SVM 0.4, PstLM 1

Warnings and Safety

- NOTE: The overall energy efficiency and light distribution of any installation that uses these lamps will be determined by the design of the installation.
- Installation must be done according to the installation diagrams provided with the lamp or available online. Installation must be done by a certified professional.

Product data

General Information		Color Designation	
Cap-Base	G13	White (WH)	
Nominal lifetime	50,000 hour(s)	Correlated Color Temperature (Nom)	3000 K
Switching Cycle	200,000	Luminous Efficacy (rated) (Nom)	93 lm/W
Lighting Technology	LEDtube	Color Consistency	<6
Flux measurement reference	Sphere	Color rendering index (CRI)	80
Warranty period	3 years	LLMF At End Of Nominal Lifetime (Nom)	70 %
Light Technical		Photobiological safety according to EN 62471	RG0
Color Code	830 [CCT of 3000K]	Operating and Electrical	
Beam Angle (Nom)	240 degree(s)	Line Frequency	50 to 60 Hz
Luminous Flux	750 lm	Input Frequency	50 to 60 Hz
		Power Consumption	8 W

CorePro LED tube EM/Mains T8

Lamp Current (Nom)	46 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	18W TL-D
Inrush current at mains	4.27
Max. lamp no. on MCB B type 10A - Mains	119
Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	154
Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	24
Max. lamp no. on MCB B type 16A - Mains	191
Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	246
Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	39
Ballast Compatibility	EM/Mains

Temperature

T-Case Maximum (Nom)	50 °C
----------------------	-------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Frosted
Bulb Material	Glass
Product Length	600 mm
Bulb Shape	T8
Net Weight (Piece)	0.220 kg

Approval and Application

Energy Efficiency Class	F
Energy Saving Product	Yes
Approval Marks	RoHS compliance CE marking KEMA Keur certificate
Energy Consumption kWh/1000 h	8 kWh
EPREL Registration Number	1827708
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	Yes
Wireless Technology	Not applicable

Product Data

Order product name	CorePro LEDtube 600mm 8W 830 T8
Full product name	CorePro LEDtube 600mm 8W 830 T8
Full product code	871951448638600
Order code	929003577132
Material Nr. (12NC)	929003577132
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514486386
Numerator - Packs per outer box	20
EAN/UPC - Case	8719514486393


Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LEDtube 600mm 8W 830 T8	25.7 mm	28 mm	588.5 mm	595.5 mm	602.5 mm

CorePro LED tube EM/Mains T8


Photometric data



Spectral Power Distribution Colour - CorePro LEDtube 600mm 8W 830 T8




Light Distribution Diagram - CorePro LEDtube 600mm 8W 830 T8




General uniform lighting - CorePro LEDtube 600mm 8W 830 T8

Lifetime



Life Expectancy Diagram



FailureRate

CorePro LED tube EM/Mains T8

Lifetime



LifetimeVsTc

Lumen Maintenance Diagram - CorePro LEDtube 600mm 8W 830 T8

