



CorePro LED PLL



CorePro LED PLL EM/Mains 8W 840 4P

CorePro, LED, PL-L, EM, 218 mm, 8 W, 18W PL-L, 4000 K, 1000 lm, CRI 80, 30000 hour(s)

CorePro, LED, PL-L, EM, 218 mm, 8 W, LED alternative to 18W PL-L, 4000 K, 1000 lm, CRI 80, 30000 hour(s), 125 lm/W, EEL E, 2G11, Beam angle 160 degree(s), Glass, RGO, SDCM 6, PF 0.9, IP20, SVM 0.4, PstLM 1

Product data

General Information	
Cap-Base	2G11
Nominal lifetime	30,000 hour(s)
Switching Cycle	200,000
Lighting Technology	LED
Flux measurement reference	Sphere
Warranty period	3 years
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	160 degree(s)
Luminous Flux	1,000 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	125 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RGO


Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	8 W
Lamp Current (Nom)	42 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	18W PL-L
Inrush current at mains	8
Max. lamp no. on MCB B type 10A - Mains	90
Max. lamp no. on MCB B type 10A - EM ballast without Compensation Capacitor.	180
Max. lamp no. on MCB B type 10A - EM ballast with Compensation Capacitor.	30
Max. lamp no. on MCB B type 16A - Mains	150
Max. lamp no. on MCB B type 16A - EM ballast without Compensation Capacitor.	290

CorePro LED PLL

Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	49
Ballast Compatibility	EM
Temperature	
T-Case Maximum (Nom)	70 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Glass
Product Length	218 mm
Bulb Shape	PL-L
Net Weight (Piece)	0.085 kg
Approval and Application	
Energy Efficiency Class	E
Energy Saving Product	Yes
Approval Marks	RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	8 kWh
EPREL Registration Number	1370824


CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) – Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 °C to 45 °C
Application Conditions	
Wireless Technology	Not applicable
Product Data	
Order product name	CorePro LED PLL EM/Mains 8W 840 4P
Full product name	CorePro LED PLL EM/Mains 8W 840 4P
Full product code	872016915701900
Order code	929003592302
Material Nr. (12NC)	929003592302
Numerator – Quantity Per Pack	1
EAN/UPC – Product/Case	8720169157019
Numerator – Packs per outer box	10
EAN/UPC – Case	8720169157026

Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLL EM/Mains 8W 840 4P	17 mm	38 mm	156 mm	218 mm	224 mm


Photometric data



General uniform lighting - CorePro LED PLL EM/Mains 8W 840 4P




Spectral Power Distribution Colour - CorePro LED PLL EM/Mains 8W 840 4P




Light Distribution Diagram - CorePro LED PLL EM/Mains 8W 840 4P

Lifetime





Lumen Maintenance Diagram - CorePro LED PLL EM/Mains 8W 840 4P



FailureRate

Lifetime



Life Expectancy Diagram



LifetimeVsTc

Lumen Maintenance Diagram - CorePro LED PLL EM/Mains 8W 840 4P

