

MASTER - LED HID SON-T - Ultra Efficient



MAS LED SON-T UE M 8Klm 42.8W 727 E40

LED SON-T, Tubular, Mains only, 42.8 W, SON-T 100W, E40, 2700 K, 8000 lm, CRI 70, 50000 hour(s)

LED SON-T, Tubular, Mains only, 42.8 W, LED alternative to SON-T 100W, E40, 2700 K, 8000 lm, CRI 70, 50000 hour(s), 186 lm/W, EEL B, PF 0.9, Beam angle 300 degree(s), Glass, RG1, IP65, SVM 1.6, PstLM 1

Warnings and Safety

• Installation should always be performed by a qualified electrician or installer. Use the installation guide for instructions.

Product data

General Information	
Cap-Base	E40
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED SON-T
Flux measurement reference	Sphere
Warranty period	5 years
Light Technical	
Color Code	727 [CCT of 2700K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	8,000 lm

Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	186 lm/W
Color Consistency	<6
Color rendering index (CRI)	70
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	42.8 W

MASTER - LED HID SON-T - Ultra Efficient

Lamp Current (Nom)	183 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
Inrush current at mains	24.4
Max. lamp no. on MCB B type 10A - Mains	8
Max. lamp no. on MCB B type 10A - EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 10A - EM ballast with Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - Mains	14
Max. lamp no. on MCB B type 16A - EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - EM ballast with Compensation Capacitor.	-
Wattage Equivalent (LED HID only)	SON-T 100W
Ballast Compatibility	Mains only

Temperature

T-Case Maximum (Nom)	49.79 °C
----------------------	----------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	Tubular
Net Weight (Piece)	0.225 kg

Approval and Application

Energy Efficiency Class	B
Energy Saving Product	Yes
Energy Consumption kWh/1000 h	43 kWh
EPREL Registration Number	2096242
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	1.6
Ambient temperature range	-30 to +45 °C


Application Conditions

can it be used in closed luminaires	Yes
Wireless Technology	Not applicable

Product Data

Order product name	MAS LED SON-T UE M 8Klm 42.8W 727 E40
Full product name	MAS LED SON-T UE M 8Klm 42.8W 727 E40
Full product code	872016924037700
Order code	929003677502
Material Nr. (12NC)	929003677502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169240377
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169240384


Dimensional drawing



Product	D	C
MAS LED SON-T UE M 8Klm 42.8W 727 E40	53 mm	236 mm


MASTER - LED HID SON-T - Ultra Efficient

Dimensional drawing




Product	D	C
MAS LED SON-T UE M 8Klm 42.8W 727 E40	53 mm	236 mm


Photometric data



Spectral Power Distribution Colour - MAS LED SON-T UE M 8Klm 42.8W 727 E40




Light Distribution Diagram - MAS LED SON-T UE M 8Klm 42.8W 727 E40




MASTER - LED HID SON-T - Ultra Efficient

Photometric data




Spectral Power Distribution Colour - MAS LED SON-T UE M 8Klm 42.8W 727 E40




Light Distribution Diagram - MAS LED SON-T UE M 8Klm 42.8W 727 E40

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS LED SON-T UE M 8Klm 42.8W 727 E40

