

PHILIPS

MAS LEDtube VLE 1200mm 13.1W/15.5W 840T8

929004356502





MASTER Value, LEDtube, T8, EM/Mains, 1200 mm, 13.1 W, 15.5 W, 36W TL-D, 4000 K, 2100 lm, 2500 lm, CRI 80, 75000 hour(s)



MASTER Value, LEDtube, T8, EM/Mains, 1200 mm, 13.1 W, 15.5 W, LED alternative to 36W TL-D, 4000 K, 2100 lm, 2500 lm, CRI 80, 75000 hour(s), 161 lm/W, EEL C, G13, Beam angle 190 degree(s), Glass, 0 %, RG0, SDCM 6, PF 0.9, IP20, SVM 0.4, PstLM 1

General Information

Cap-Base	G13
Nominal lifetime	75,000 hour(s)
Switching Cycle	200,000
Lighting Technology	LEDtube
Flux measurement reference	Sphere
Warranty period	5 years

Light Technical

Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	190 degree(s)
Luminous Flux	2,100 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	161 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG0
All-in Type	All-in, Multi Lumen

Operating and Electrical

Input Frequency	50 to 60 Hz
Power Consumption	13.1 W
Lamp Current (Max)	80 mA
Lamp Current (Min)	70 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	36W TL-D
Inrush current at mains	5.4/5.6
Max. lamp no. on MCB B type 10A - Mains	135/110
Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	125/110
Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	20
Max. lamp no. on MCB B type 16A - Mains	220/180
Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	200/170
Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	30
Ballast Compatibility	EM/Mains

Temperature

T-Case Maximum (Nom)	55 °C

Controls and Dimming

Dimmable	No

Mechanical and Housing

Bulb Finish	Frosted
Bulb Material	Glass
Product Length	1,200 mm
Bulb Shape	T8
Net Weight (Piece)	0.190 kg

Approval and Application

Energy Efficiency Class	C
Energy Saving Product	Yes
Approval Marks	RoHS compliance
Energy Consumption kWh/1000 h	16 kWh
EPREL Registration Number	2519085
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C
Post-consumer recycled plastic material ratio	0 %

Application Conditions

Wireless Technology	Not applicable

Sustainability Data


Product non-virgin material ratio	0 %

Product Data

Order product name	MAS LEDtube VLE 1200mm 13.1W/ 15.5W 840T8
Full product name	MAS LEDtube VLE 1200mm 13.1W/ 15.5W 840T8
Full product code	872110313913900
Order code	929004356502


Material Nr. (12NC)	929004356502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8721103139139
Numerator - Packs per outer box	20
EAN/UPC - Case	8721103139146

Dimensional drawing




Product	D1	D2	A1	A2	A3
MAS LEDtube VLE 1200mm 13.1W/15.5W 840T8	25.7 mm	28 mm	1,199.4 mm	1,206.5 mm	1,213.6 mm


Photometric data



General uniform lighting - MAS LEDtube VLE 1200mm 13.1W/ 15.5W 840T8




Spectral Power Distribution Colour - MAS LEDtube VLE 1200mm 13.1W/15.5W 840T8




Light Distribution Diagram - MAS LEDtube VLE 1200mm 13.1W/15.5W 840T8


Lifetime




Lumen Maintenance Diagram - MAS LEDtube VLE 1200mm 13.1W/15.5W 840T8




Lumen Maintenance Diagram - MAS LEDtube VLE 1200mm 13.1W/15.5W 840T8



LEDtube-75K-5575-FailureRate-LED



Life Expectancy Diagram



LifetimeVsTc

Related Documents

Documents and certificates	Document Name	Download
Installation Instructions	66357991-139078-LED-BULB-NDLR-QIG-INI.pdf	Download
Environmental Product Declaration	Philips-Master-Value-LED-tube-T8-COMF-7389584-Ref-929004356502-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	MAS-LEDtube-VLE-1200mm-15-5W-840-T8-9290043565-IES.IES	Download
LDT File	MAS-LEDtube-VLE-1200mm-13-1W-15-5W-840-T8-9290043565-LDT.ldt	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.