



# MSR Gold™ FastFit

## MSR Gold™ 2000/2 FastFit 1CT/8

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General information		Operating and electrical	
Cap-Base	PGJX50 [ PGJX50]	Power (Nom)	2000 W
Operating Position	UNIVERSAL [ Any or Universal (U)]	Lamp Current (Nom)	15.4 A
Main Application	Entertainment	Ignition Supply Voltage (Min)	198 V
Life to 50% Failures (Nom)	750 h	Chromaticity Coordinate Y (Nom)	322
System Description	FastFit	Correlated Color Temperature (Nom)	7500 K
Light technical		Luminous Efficacy (rated) (Nom)	80 lm/W
Color Code	2	Color Rendering Index (Nom)	88
Luminous Flux (Min)	138000 lm		
Luminous Flux (Nom)	160000 lm		
Chromaticity Coordinate X (Nom)	297		

# MSR Gold™ FastFit

## Controls and dimming

Dimmable Yes

## Mechanical and housing

Cap-Base Information PGJX50

## Luminaire design requirements

Bulb Temperature (Max) 950 °C

Pinch Temperature (Max) 500 °C

## Product data

Full product code 872790090830500

Order product name MSR Gold™ 2000/2 FastFit 1CT/8

EAN/UPC - Product 8727900908305

Order code 928106105114

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 8

Material Nr. (12NC) 928106105114

Net Weight (Piece) 0.147 g

## Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR Gold™ 2000/2 FastFit 1CT/8	34 mm	8.0 mm	66 mm	68 mm	67 mm	134 mm	50 mm

MSR Gold™ 2000/2 FastFit 1CT/8

