


MSR Gold™ MiniFastFit (Touring/Stage)

| Controls and dimming | |
|-------------------------------|-----------------|
| Dimmable | Yes |
| Mechanical and housing | |
| Cap-Base Information | PGJX28 |
| Luminaire design requirements | |
| Bulb Temperature (Max) | 950 °C |
| Pinch Temperature (Max) | 500 °C |
| Product data | |
| Full product code | 871829115828800 |

| | |
|---------------------------------|----------------------------------|
| Order product name | MSR Gold™ 400 MiniFastFit 1CT/16 |
| EAN/UPC - Product | 8718291158288 |
| Order code | 928194005114 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 16 |
| Material Nr. (12NC) | 928194005114 |
| Net Weight (Piece) | 0.053 kg |

Dimensional drawing



| Product | D (max) | O | L (min) | L (max) | L | C (max) | F (max) | F | F (min) |
|---|------------|-----------|------------|------------|----------|------------|------------|----------|------------|
| MSR Gold™ 400 MiniFastFit 1CT/16 | 23.2 mm | 3.0 mm | 55 mm | 57 mm | 56 mm | 111 mm | 36.5 mm | 36 mm | 35.3 mm |

MSR Gold™ 400 MiniFastFit 1CT/16

