

**PRODUCT REQUIREMENT SHEET**

See LV-75-34



**ELECTRICAL DATA**  
(with the specified ballast)

	Measuring Point	Value	Unit	Tolerance
Lamp Wattage	0h	1900	W	Nom
Lamp Voltage	0h	210	V	± 20
Lamp Current	0h	10	A	Nom
Power Density	0h	NA	W/cm	Nom
Ignition Supply Voltage	0h	350	V	min
Ignition Time	0h	20	s	Max
Warm-Up Time		2	min	Max
Re-Ignition Time		10	min	Max

**UV RADIATION**  
(with the specified ballast)

	Measuring Point	Value	Unit	Tolerance
UV-A (315-400 nm)	0h	NA	µW/cm <sup>2</sup>	± 10%
UV-B (280-315 nm)	0h	* 650	µW/cm <sup>2</sup>	± 10%
UV-C (200-280 nm)	0h	* NA	µW/cm <sup>2</sup>	± 10%
DIAZO (350-460 nm)	0h	3800	µW/cm <sup>2</sup>	± 10%
UV Maintenance	750h	80	%	min
Doping	Gallium			
Quartz Tube	Ozone free			

**GENERAL SPECIFICATIONS**  
(in operating conditions)

	Value	Unit	Tolerance
Bulb Temperature	750 950	°C	min Max
Pinch Temperature	350	°C	Max
Lamp Position	Horizontal		

**BALLAST DESCRIPTION**

Ballast Reference	BHL 2000L18		
Ballast Power (indicative)	2000 W	Supply Voltage	380 V
Supply Wave Form	Sine wave	Frequency	50 Hz
Ignitor Reference	380 MZN 4000	Capacitor Reference	30+30 µF

1	0833	2	0833	3	0000	4	m : xxx g	5		6		7		8	
SUPERSEDES :		UV LAMP						9280 808 06000		30/09/2021					
9280 808 06000		HPM 2010						0833/000							
0833/000 p190-2															
Of 19/09/2016															
REF. :	PDM UV-534	DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10	A4						
NOM :	PI120	VALIDATION : SN928			DR. FISCHER Europe										
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															