

Aquastar T8

F25W/30/Aquastar

0002226



Range Features

- Light colour: 10000 Kelvin (simulating the tropical light spectrum)
- Promotes the growth of coral and aquatic plants through natural red and blue sections of the light spectrum
- Excellent lighting performance
- Applications
- For all biological organisms in fresh and marine water aquariums



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Colour temperature (K)	10000
Dimmable	Yes
EAN code	5410288022260
Cap/Base	G13
Туре	AquaStar
Watt (Nominal) (W)	25
Ordering number	0002226
Luminous flux (Rated) (lm)	1500
Voltage (V)	84

DATA TABLE

General	data
Concrai	autu

Average life (Nominal) (h)	10000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288022260
Fixture rating	Open
IEC Reference	IEC 60081



Aquastar T8

F25W/30/Aquastar

0002226

IEC Reference 2	IEC 61195
Cap/Base	G13
Lamp mercury content (mg)	10
Туре	AquaStar
Ordering number	0002226
Range features	Light colour: 10000 Kelvin (simulating the tropical light spectrum) Promotes the growth of coral and aquatic plants through natural red and blue sections of the light spectrum Excellent lighting performance Applications For all biological organisms in fresh and marine water aquariums
Product name	F25W/30/Aquastar
Special purpose lamp	Yes
Transformer required	No
Sales pack quantity	25
E-number SE	8356652
Optical data	
Colour temperature (K)	10000
Colour temperature (K) Luminous flux (Nominal) (lm)	10000 1500
-	
Luminous flux (Nominal) (lm)	1500
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im)	1500
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data	1500 1500
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A)	1500 1500 0.36
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A) Watt (Nominal) (W)	1500 1500 0.36 25
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W)	1500 1500 0.36 25 25
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V)	1500 1500 0.36 25 25
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data	1500 1500 0.36 25 25 84
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D	1500 1500 0.36 25 25 84
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L	1500 1500 0.36 25 25 84
Luminous flux (Nominal) (Im) Luminous flux (Rated) (Im) Electrical data Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A	1500 1500 0.36 25 25 84 26 756.4 742.2

TECHNICAL DRAWINGS

