

# XBO 150 W/4

XBO Xenon short-arc lamps without reflector | Xenon short-arc lamps without reflector



### Product family benefits

- Very high luminance (point light source)
- Continual color quality, irrespective of lamp type and lamp wattage
- Constant light color throughout the life of the lamp
- Long lamp life

### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- High color rendering index: R<sub>a</sub> >
- Continuous spectrum in the visible range
- High arc stability
- Hot restart capability
- Dimmable
- Instant light on starting







### Product datasheet

### Technical data

### **Electrical data**


Lamp wattage	130 W
Lamp current	7.5 A
Type of current	DC

### Photometrical data

Nominal luminous flux	3000 lm		
Luminous intensity	300 cd <sup>1)</sup>		
Luminance	15000 cd/cm <sup>2</sup> 1)		

 $<sup>^{1)}</sup>$  Typical initial photometric value

### **Dimensions & weight**



Length	150.0 mm	
Length with base excl. base pins/connection	127.00 mm	
Product weight	100.00 g	

### Lifespan

Lifespan	1200 h

### Additional product data

Base anode (standard designation)	SFc12-4
Base cathode (standard designation)	SFcX12-4

### Capabilities

Cooling	Forced
Burning position	s15 <sup>1)</sup>
Application	Other

# Product datasheet

# Country specific information


Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300508382	OSRXBO1504	-	-	-
4050300508382	OSRXBO1504	-	-	-

<sup>1)</sup> Anode (+) on top

#### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.



#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300508382	XBO 150 W/4	Folding carton box 1	100 mm x 59 mm x 245 mm	1.45 dm <sup>3</sup>	191.00 g
4050300508399	XBO 150 W/4	Shipping carton box 10	259 mm x 315 mm x 216 mm	17.62 dm³	1726.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

Further technical information on XBO lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.