

## OTe 35/220...240/700 PC

OPTOTRONIC Phase-cut OTE | Compact constant current LED drivers



### Areas of application

- Optional cable clamp E-style for independent mounting
- Suitable for indoor installations
- Suitable for indoor SELV installations

### Product family benefits

- Compact housing for mounting in very tight spaces
- Compatible with the most common leading-edge and trailing-edge phase dimmers

### Product family features

- Dimmable via leading edge/trailing edge
- Type of protection: IP20



## Technical data

### Electrical data

Nominal input voltage	220...240 V
Mains frequency	50/60 Hz
Input voltage AC	195...264 V <sup>1)</sup>
Power factor $\lambda$	0.95/0.90 <sup>2)</sup>
ECG efficiency	87 % <sup>3)</sup>
Device power loss	5.25 W <sup>4)</sup>
Power loss in stand-by mode	<1 W <sup>5)</sup>
Inrush current	< 10 A <sup>6)</sup>
Max. ECG no. on circuit breaker 10 A (B)	32
Max. ECG no. on circuit breaker 16 A (B)	50
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Nominal output voltage	27...50 V <sup>7)</sup>
U-OUT (working voltage)	58 V
Nominal output current	700 mA <sup>8)</sup>
Output current tolerance	±5 %
Output ripple current (100 Hz)	< 35 % <sup>9)</sup>
Output PSTLM	≤1
Output SVM	≤0.8
Nominal output power	35 W <sup>10)</sup>
Galvanic isolation	SELV

<sup>1)</sup> Permitted voltage range

<sup>2)</sup> Full load at 230 V/Minimum load at 230 V

<sup>3)</sup> At full load and 230 V

<sup>4)</sup> Maximum

<sup>5)</sup> No load condition

<sup>6)</sup>  $t_{\text{width}} = 250 \mu\text{s}$  (measured at 50 %  $I_{\text{peak}}$ )


<sup>7)</sup> Maximum <58 V

<sup>8)</sup> ±5%

<sup>9)</sup> Typical

<sup>10)</sup> Partial load 19...35 W

## Dimensions & weight



Mounting hole spacing, length	146.0 mm
Mounting hole spacing, width	15.0 mm
Product weight	165.00 g
Cable cross-section, input side	0.75...2.5 mm <sup>2</sup> <sup>1)</sup>
Cable cross-section, output side	0.5...2.5 mm <sup>2</sup> <sup>1)</sup>
Wire preparation length, input side	5.0 mm
Wire preparation length, output side	5.0 mm
Length	153.0 mm
Width	54.0 mm
Height	36.0 mm

<sup>1)</sup> Flexible / Solid leads

## Colors & materials

Casing material	Plastic
-----------------	---------

## Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	75 °C <sup>1)</sup>
Max.housing temperature in case of fault	110 °C
Temperature range at storage	-40...+85 °C
Permitted rel. humidity during operation	5...85 % <sup>2)</sup>

<sup>1)</sup> Maximum at the T<sub>c</sub>-point

<sup>2)</sup> Maximum 56 days/year at 85 %

## Lifespan

ECG lifetime	50000 h <sup>1)</sup>
--------------	-----------------------

<sup>1)</sup> At T<sub>case</sub> = 65°C at T<sub>c</sub> point / 10% failure rate

## Product datasheet

### Additional product data

Encapsulated	No
--------------	----

### Capabilities

Dimmable	Yes
Dimming interface	Phase Cut <sup>1)</sup>
Dimming range	10...100 %
Dimming method	Amplitude Modulation
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
No-load proof	Yes
Max. cable length to lamp/LED module	2.0 m
Suitable for fixtures with prot. class	I / II
Type of connection, output side	Push terminal

<sup>1)</sup> Leading edge

### Programming

Tuner4TRONIC	No
Tuner4TRONIC Field App	No



### Certificates & standards

Approval marks – approval	CE / ENEC 10 / VDE / CB / C-Tick
Standards	Acc. to IEC 61347-1/Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to CISPR 15/Acc. to IEC 61000-3-2/Acc. to IEC 61000-3-3/Acc. to IEC 61547
Protection class	II
Type of protection	IP20

### Logistical data







Commodity code	850440829000
----------------	--------------

### Download Data

File
 Product Datasheet 342830_Datasheet OTe 35220-240700 PC
 Certificates OTE 35 700 PC CB DE1 63216 040320

## Product datasheet

---

	Certificates OT ENEC 40038447 030720
	Declarations of conformity 727840_Declaration OTe 35
	Declarations of conformity OTE PC CE 3365230 051119
	Installation/Operation notice OT PC dimmer list (EN)
	Installation/Operation notice 343883_Dimmer Compatibility List_OTe 35220-240700 PC
	CAD data 3-dim 343465_CAD OTe 35220-240700 PC

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321825520	OTe 35/220...240/700 PC	Shipping carton box 10	276 mm x 98 mm x 166 mm	4.49 dm <sup>3</sup>	1812.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.