

# 64796 CP/91 2500W 230V 12/CS 1/SKU



#### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

#### Technical data

### General product information

Product Number	54538
Product Name	64796 CP/91 2500W 230V 12/CS 1/SKU
Ordering Abbreviation	64796 CP/91 2500W 230V 12/CS 1/SKU
Brand Name	OSRAM
LIF Code	CP/90

### Electrical data

Nominal Wattage	2500 W
Nominal Voltage	230 V
Type of Current	AC

## Light technical data

Luminous Flux	65000 lm
Light Center Length - LCL (in)	3.54 in
Light Center Length - LCL (mm)	90 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	400 h


# Physical attributes

Base	G22 MEDIUM BIPOST		
Bulb Shape	T10		
Length I (in)	6.89 in		
Length I (mm)	175 mm		
Diameter d (in)	1.339 in		
Diameter d (mm)	34.00 mm		
Distance a (in)	3.540 in		
Distance a (mm)	90 mm		
Filament	C13D		

# Additional product data

Operating Position	s90

### Product datasheet



### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54538	4008321653987	Folding box (SKU)	1	2.2 in x 2.2 in x 7.5 in	0.4 lb
54538	4008321984302	Shipping box (Case)	12	10 in x 8.7 in x 7.6 in	4.6 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.