

## XBO 3000 W/DHP L OFR

XBO DHP for digital cinema projection | Xenon short-arc lamps




### Areas of application

- Cinema projection

### Product family features

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range




# Product datasheet

## Technical data

### Electrical data

Nominal current	103 A
Nominal wattage	3000.00 W
Current control range	76...111 A
Nominal voltage	29.0 V

### Dimensions & weight



Diameter	60.0 mm
Length	345.0 mm
Length with base excl. base pins/connection	295.00 mm
Cable/wire length, input side	130 mm
Light center length (LCL)	123.0 mm <sup>1)</sup>
Electrode gap cold	5.0 mm
Product weight	623.00 g
Cable length	130.0

<sup>1)</sup> Distance from end of base to tip of electrode (cold)

### Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

### Lifespan

Lifespan	1900 h
Service Warranty Lifetime	2100 h

### Additional product data

Base anode (standard designation)	SFaX27-14x80
Base cathode (standard designation)	SFc27-16/55

## Product datasheet

### Capabilities

<b>Cooling</b>	Forced
<b>Burning position</b>	s15/p15 <sup>1)</sup>

<sup>1)</sup> For vertical burning position: anode (+) on top

### Environmental information

<b>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</b>	
<b>Date of Declaration</b>	28-01-2022
<b>Primary Article Identifier</b>	4052899212886   4052899235908   4052899317277   4062172030502
<b>Candidate List Substance 1</b>	Lead
<b>CAS No. of substance 1</b>	7439-92-1
<b>Safe Use Instruction</b>	The identification of the Candidate List substance is sufficient to allow safe use of the article.
<b>Declaration No. in SCIP database</b>	42B5A623-65C3-4FC7-B272-E9973BA1C9EC

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172030502	XBO 3000 W/DHP L OFR	Shipping carton box 1	500 mm x 204 mm x 204 mm	20.81 dm <sup>3</sup>	1419.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---