

BAA



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54924
Product Name	BAA 28V 24/CS 1/SKU
Ordering Abbreviation	BAA
Brand Name	OSRAM
General Description	75 watt, tungsten halogen, low to medium voltage with reflector
Application	Projector

Electrical data

Nominal Wattage	75 W
Nominal Voltage	28 V
Type of Current	AC

Light technical data

Working Distance a (in)	12.975 in
Working Distance a (mm)	332.7 mm
Color Temperature	3000 K
Color Rendering Index	100
Average Rated Life	2000 h

Physical attributes

Bulb Shape	MR16
Maximum Overall Length (in)	1.689 in
Maximum Overall Length (mm)	43.3 mm
Length l (in)	1.486 in
Length l (mm)	38.1 mm
Length l max. (in)	1.486 in
Length l max. (mm)	38.1 mm
Diameter d (in)	39.366 in
Diameter d (mm)	999.90 mm
Reflector Coating	WHITE

Additional product data

Operating Position	Any
Class	C (gas)
Lamp Type	MR16

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54924	0046135549243	Folding box (SKU)	1		
54924	10046135549240	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.