

ELC 64653 HLX 250W 24V 20/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54212		
Product Name	ELC 64653 HLX 250W 24V 20/CS 1/SKU		
Family Brand Name	XENOPHOT (HLX)		
Application	Overhead projection, fiber-optic, entertainment		
LIF Code	A1/259 - p (Operating Position) = Horizontal - Lumens refers to screen lumens.		
Product Remark			

Electrical data

Nominal Wattage	250 W		
Nominal Voltage	24 V		
Type of Current	AC		

Light technical data

Luminous Flux	900 lm		
Working Distance a (in)	1.378 in		
Working Distance a (mm)	35 mm		
Color Rendering Index	100		
Average Rated Life	50 h		

Physical attributes

Base	GX5.3			
Bulb Shape	MR51			
Maximum Overall Length (in)	1.752 in			
Maximum Overall Length (mm)	44.5 mm			
Length l (in)	1.752 in			
Length l (mm)	44.5 mm			
Length l max. (in)	1.752 in			
Length l max. (mm)	44.5 mm			
Diameter d (in)	2.008 in			
Diameter d (mm)	51.00 mm			
Filament	C-8			
Reflector Coating	51.00			

Additional product data

Operating Position	p 90/15

Product datasheet

Cla	ass						
ě	ĕ	*	ő	*		*	*
e	*	*	*	"@	1	"" (9
9		¢.		-1		-1	- 38
		٠					

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight	
54212	4052899329348	Folding box (SKU)	1	1.8 in x 1.8 in x 2.3 in	0.1 lb	
54212	4052899329355	Shipping box (Case)	20	9.4 in x 4.1 in x 4.8 in	1.7 lb	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.