

## 64337 A 48-15

Halogen lamps with reflector, current-controlled, 45...48 W



### Product family benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

### Product family features

- Dimmable
- Available with connector combinations A, B, C/Z on request
- Infrared radiation output that provides light in the worst of conditions



# Product datasheet

## Technical data

### Product information

Order reference	64337
-----------------	-------


### Electrical data

Lamp current	6.6 A
Nominal wattage	48.00 W

### Photometrical data

Luminous intensity	20000 cd
Axial luminous intensity	23000 cd

### Dimensions & weight



Diameter	50.4 mm
Length	45.0 mm
Length with base excl. base pins/connection	45.00 mm

### Lifespan

Lifespan	1500 h
----------	--------

### Capabilities

Dimmable	Yes
Burning position	Horizontal
Mains terminals	Leads w/female flat connectors

### Country specific categorizations

Order reference	64337
-----------------	-------

## Product datasheet

---

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321102737	OSRH64337A4820	-	-	-
4008321102737	OSRH64337A4820	-	-	-

## Product datasheet

---

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321102737	64337 A 48-15	Folding carton box 1	63 mm x 50 mm x 50 mm	0.16 dm <sup>3</sup>	38.34 g
4008321102744	64337 A 48-15	Shipping carton box 20	257 mm x 131 mm x 109 mm	3.67 dm <sup>3</sup>	856.80 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### References / Links

For more information on airfield lamps see the brochure:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---